

SmartPower RPS



Mechanical

Dimensions	442.4 x 325.6 x 43.7 mm (17.4 x 12.8 x 1.7")
Weight	5.5 kg (12.13 lb)
Enclosure material	SGCC steel

Hardware

Networking interface	(1) GbE RJ45 port
Management interface	Ethernet
Power method	(1) Universal AC input 100–240V AC
Power supply	Internal 350W AC/DC Internal 645W AC/DC
Max. power consumption	995W
System total DC output power budget	52V DC, 11.54A (600W) 11.5V DC, 30.44A (350W)
Supported models*	UDM-Pro UDM-SE UXG-Pro UNVR UNVR-Pro USW-Pro-24 USW-Pro-48 USW-Pro-24-PoE USW-Pro-48-PoE USW-Enterprise-24-PoE USW-Enterprise-48-PoE USW-EnterpriseXG-24 USW-Pro-Aggregation
	<small>*Maximum power consumption per device model</small>
ESD/EMP protection	Air: ± 16 kV, contact: ± 12 kV
Operating temperature	-5 to 45° C (23 to 113° F)
Operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

LEDs

System	Status
RJ45	Link/activity
USP RPS	Activity

