

Product data sheet

Specifications



Easy PDU, Switched, 1U, 16A, 230V, (8)C13

EPDU1016S

Overview

Lead time Usually in Stock

General

Provided equipment Horizontal mounting brackets
Installation guide
Cable

Physical

Cable length 2.50 m

Colour Black

Depth 20 cm

Height 4.44 cm

Net weight 2.8 kg

Width 48.2 cm

Input

Input current limits 16 A

Load capacity 3680 VA

Network frequency 50/60 Hz

Plug standard IEC 60320 C20

Input voltage 200 V
208 V
230 V

Output

Number of power socket outlets 8 IEC 60320 C13

Conformance

Product certifications CE
EAC
TÜV

Environmental

Ambient air temperature for operation -5...45 °C

Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	3.6 kg
Package 1 Height	8 cm
Package 1 width	56 cm
Package 1 Length	26 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------