

Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

APDU9981EU3

Overview

Lead time Usually in Stock

General

Provided equipment Installation guide
Rack mounting brackets
Safety guide

Physical

Cable length 1.83 m
Colour Black
Depth 4.6 cm
Height 179.2 cm
Net weight 7 kg
Width 5.5 cm

Input

[In] rated current 16 A
Max line current 16 A
Communication port protocol SNMP
Redfish
Input current limits 16 A
Load capacity 11000 VA
Network frequency 50/60 Hz
Plug standard IEC 60309 16 A 3P + N + PE
Input voltage 400 V 3 phases

Output

Number of power socket outlets 21 IEC 60320 C13
3 IEC 60320 C19

Conformance

Product certifications cUL listed
FCC part 15 class A
UL listed

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
------------------	--

Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Batteries & Runtime

Communication network type	10/100/1000BASE-T
-----------------------------------	-------------------

Packing Units

Package 1 Weight	8.95 kg
Package 1 Height	200.2 cm
Package 1 width	16.5 cm
Package 1 Length	11.4 cm
Number of Units in Package 3	48

Contractual warranty

Warranty	3 years repair or replace
-----------------	---------------------------
