

# Product data sheet

Specifications



## APC Easy UPS BVX 2200VA, 230V, AVR, Schuko Sockets

BVX2200LI-GR

### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	User manual
Max runtime	240 min
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Physical

Cable length	1.22 m
Colour	Black
Depth	39 cm
Height	19 cm
Mounting support	Floor
Mounting preference	No preference
Net weight	12.2 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	14 cm

### Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	Schuko
Input voltage limits	140...300 V 230 V AC
Number of cables	1

Input voltage	230 V AC 1 phase
Cos phi	0.54
<b>Output</b>	
Rated power in W	1200 W
Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Schuko
Curve equation	Efficiency
Curve fixed loss	0.0195
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0.0102
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Output voltage	230 V AC 1 phase
Maximum configurable power in VA	2200 VA
Rated power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1 EN/IEC 62040-2 CE
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
Show note OP temperature	No
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Liquid value	0
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery curve	C
Battery power in VAH	190 VAh runtime 216 VAh capacity
Battery life	2...3 year(s)
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0

## Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

## Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

## Packing Units

Package 1 Weight	13.2 kg
Package 1 Height	29.7 cm
Package 1 width	23.5 cm
Package 1 Length	49.5 cm
SCC14	10731304404627

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------