

Aastra 6865i

Exceptional Value in a Fully Featured, Expandable IP Phone

The Aastra 6865i offers exceptional flexibility in a true enterprise grade SIP desktop phone that can support up to 9 lines, has Dual Gigabit Ethernet ports and features a large 3.4" 128x48 pixel LCD display with soft white backlighting and large fonts making the screen easy to read in any lighting conditions. With its 8 programmable keys, XML capabilities, native DHSG/EHS headset support, a true HD handset and a speakerphone that delivers remarkable wideband HD audio quality, the Aastra 6865i SIP phone is ideally suited for the small to large business market that needs Gigabit throughput for PC connectivity.



Aastra 6865i

Key Features and Benefits

Remarkable Audio

All 6800i Series SIP phones feature Aastra's high definition Hi-Q™ audio technology to deliver enhanced performance and voice clarity. Integrating HD wideband audio codecs, advanced audio processing and hardware components that support a true wideband frequency range, the 6865i offers a superior voice experience on each audio path – handset, speakerphone or headset port – making conversations crystal clear and more life-like.

Enhanced Call Management

With an extensive storage capacity for personal directories, callers logs, redial lists, and 8 programmable keys, the Aastra 6865i is designed to easily manage access to all of the most frequently used call management features of the phone. Even more productivity enhancing features are available at the push of a button including: Shared Call Appearance (SCA), Busy Lamp Fields (BLF), 3-way conferencing, transfer, call waiting, call park, call pickup, intercom and paging. The 6865i is also an expandable desktop phone supporting up to three expansion modules further enhancing its productivity capabilities with additional programmable keys that can be used to access the broad list of advanced features offered by this powerful phone.

Flexible Headset Options

The Aastra 6865i features an innovative headset port that uniquely provides dual support for DHSG/EHS and modular 4-pin headset connections. Users with wireless headsets that support DHSG/EHS can now connect directly to the 6865i without the added cost of additional adaptors or cables.

Environmentally Friendly

All Aastra 6800i Series SIP phones have been designed to be environmentally friendly. Using dynamic PoE class reporting, the 6865i has a PoE Class 2 rating that automatically switches classes when an expansion module is connected enabling the phone and network switches to efficiently manage its power consumption. The Aastra 6865i also supports an optional Efficiency Level "V" compliant power adaptor if required. With smaller packaging that includes 100% recycled and biodegradable material, the Aastra 6800i Series is one of the most environmentally friendly family of SIP phones on the market.

Feature Keys

- ✦ Up to 9 lines with 2 dedicated line keys with LED
- ✦ 8 Programmable keys with LEDs
- ✦ 4-way navigation key with Select/OK button
- ✦ Dedicated function keys including: Conference, Transfer, Callers List, Hold, Redial, Goodbye, Options, 2 volume keys, Mute (with LED) and Speaker/Headset (with LED)

Audio and Codecs

- ✦ Aastra Hi-Q™ Audio Technology
- ✦ Hearing aid compatible (HAC) handset
- ✦ Full-duplex quality speakerphone
- ✦ Wideband handset and speakerphone
- ✦ Codecs: G.711 μ -law / A-law, G.729, G.722, AMR*, AMR-WB(G.722.2)*, G.726, iLBC, BV16, BV32, L16
- ✦ Echo cancellation
- ✦ Comfort noise utilization
- ✦ Packet loss concealment
- ✦ Voice Quality Metrics, including MOS
- ✦ DHSG/EHS and 4-pin modular headset supported

Display and Indicators

- ✦ Monochrome LCD
 - 3.4" 128x48 pixel graphical backlit display
 - Soft white backlight for user comfort in any lighting condition
- ✦ LED for call and message waiting indication

Security

- ✦ User and administrator level passwords for login
- ✦ Encryption of configuration files
- ✦ HTTPS configuration downloaded and web management
- ✦ Phone lock with PIN

- ✦ Digest Authentication
- ✦ Transport Layer Security (TLS)
- ✦ Secure Real-Time Protocol (SRTP)

XML API Capabilities

- ✦ Display control based on user actions or events
- ✦ Dynamic Phone Configuration
- ✦ RTP Streaming Control
- ✦ CTI applications
- ✦ Extensive XML documentation and sample Apps

Localization

- ✦ Multi-lingual support – English, French, Spanish, Italian, German
 - Downloadable language pack support for customization and additional language translations
- ✦ Country-Specific call progress tones and cadences
- ✦ Latin1, Latin2 Character sets

Protocol

- ✦ IETF SIP (RFC3261) and associated RFCs

Networking and Provisioning

- ✦ Dual 10/100/1000 Mbps Ethernet ports (LAN/PC)
- ✦ Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
- ✦ Support of multiple DHCP options: 2,12,42,43,60,66,77,120,132,159,160
- ✦ Time and date synchronization using SNTP
- ✦ Quality of Service support – IEEE 802.1 p/Q VLAN and priority tagging, Type of Service (TOS), and Differentiated Services Code Point
- ✦ Network Address Translation (NAT), STUN, TURN support
- ✦ Integrated HTTP/HTTPS server for web administration and maintenance including a built-in troubleshooting section

- ✦ Mass deployment via central provisioning of user configuration files – TFTP, FTP, HTTP, HTTPS
- ✦ TR-069 support
- ✦ Redundant server support
 - DNS-SRV
 - Backup proxy/registrar server support
- ✦ RTCP support (RFC1889)
- ✦ RTP streaming for Paging and Intercom applications
- ✦ IEEE 802.1x
- ✦ LLDP-MED

Expansion Modules

- ✦ Up to three Expansion Modules supported

Power

- ✦ PoE Class 2
- ✦ Dynamic PoE class changes when expansion modules are added
- ✦ Level "V" energy efficiency rated power adapters available
 - 87-00012AAA-A (Europe)
 - 87-00013AAA-A (North America)
 - D6700-0131-48-20 (Universal)

Package Content

- ✦ Aastra 6865i phone
- ✦ Handset and coil cord
- ✦ Adjustable 2-angle stand (35° & 60°)

Accessories

- ✦ M685i LCD Expansion Module – 80C00007AAA-A
- ✦ M680i Paper Expansion Module – 80C00010AAA-A
- ✦ Wall Mount Kit – 80C00011AAA-A

Part Number

- ✦ Aastra 6865i – 80C00001AAA-A

* license required