

AXIS T93E05 Protective Housing

Unobtrusive housing with compact and slim design.



- > IP66-rated
- > Ease of installation
- > Compact design
- > One cable installation

AXIS T93E Protective Housing protects the AXIS M11 Network Camera Series where a fixed camera needs to be protected but still unobtrusive.

AXIS T93E05 features IP66 protection rating against the ingress of dust and high pressure water jets from any direction. The materials used in the enclosure, in combination with the camera, make the use of a window heater unnecessary.

Various brackets and accessories are available for AXIS T93E05 Protective Housing, such as ceiling and wall brackets, column mounts and adapters. AXIS T93E05 comes with a wall bracket with an internal cable channel and ball joint.

Quick and easy installation thanks to Power over Ethernet connection. The network cable is further protected in the wall mount for tamper protection.



Technical specifications – AXIS T93E05 Protective Housing

General	
Supported cameras	AXIS M1103, AXIS M1104, AXIS M1113, AXIS M1114
Casing	Acrylate, IP66-rated Color: white NCS S 1002-B
Power	Camera powered by PoE via network cable
Environment	Indoor/outdoor
Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 15 - 100% RH (condensing)
Protection rating	IEC 60529 IP66
Approvals	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, ISO 4892-2
Weight	580 g (1.28 lb.)
Included accessories	Wall bracket, sunshield, User's Guide, Desiccant bag

More information and a configuration tool is available at www.axis.com/accessories

Dimensions: AXIS T93E05 Protective Housing and wall bracket with internal cable channel

With sunshield
 72 mm (2.8") height, 95 mm (3.7") depth, 106 mm (4.2") width, 122 mm (4.8") height, 303 mm (11.9") length.

Without sunshield
 62 mm (2.4") height, 82 mm (3.2") depth, 101 mm (3.9") width, 109 mm (4.3") height, 258 mm (10.1") length.

Max. inclination
 70°

Wall mount bracket
 180 mm (7.1") width, 204 mm (8.0") width.

Back side of wall mount bracket
 120 mm (4.7") height, 85 mm (3.4") width, 40 mm (1.6") width, 80 mm (3.1") width, 10 mm (0.4") depth.

Optional mounting accessories

Wall brackets
 Wall bracket and integrated junction box, Wall bracket ball joint, Column bracket Wall mount with ball joint.

Ceiling brackets
 Ceiling bracket and internal cable channel, Ceiling bracket ball joint, Ceiling bracket ball joint.

Wall bracket accessories
 Wall bracket adapter plate, Pole mount adapter, Corner mount, Waterproof junction box.

Other accessories

AXIS T90A White LED Illuminators

AXIS PoE products