



## 55" HIGH BRIGHTNESS 3500 NIT FANLESS LCD WITH NARROW BEZEL MODEL DS552LT4-1

The DS552LT4-1 is a 55 inch ultra high brightness professional LCD with IPS technology. With a brightness rating of 3500 nits, this display features an LED back light for incredible, high contrast picture quality and low power consumption. The DS552LT4-1 features a 21.8 mm bezel-to-bezel width, perfect for video wall applications in bright environments. The display features an integrated Android™ based media player with WiFi offering users a complete media platform, allowing playback of local files and USB/SD card media.

Screen image simulated.  
Android is a trademark of Google Inc.  
The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

### Key Features

- 3500 nits Brightness
- Fanless Thermal Management
- Integrated Android Media Player
- LED Backlit
- Blackening Defect Free in Direct Sunlight
- Fanless Thermal Management
- 1920 x1080 Full HD Native Resolution
- 10.9 mm Bezel Width

# 55" HIGH BRIGHTNESS 3500 NIT FANLESS LCD WITH NARROW BEZEL MODEL DS552LT4-1

## PANEL

LCD Panel Type	54.64 inches IPS LCD
Native Resolution	1920 x 1080
Backlight	LED
Brightness	3500 nit
Default Color Temperature	D65 (6500 K)
Contrast Ratio	3,000:1
Color Depth	8 bits
Response Time	9 ms (typ)
Viewing Angle	178° / 178°
Light Life Time	50,000 hrs (typ.)
Blackening Defect Free	Up to 110°C (230°F)
Panel Surface	AR , 2H

## POWER

Power Supply	Internal
Rated Voltage	100 V ~ 240 V, 50 Hz / 60 Hz
Power On Mode	160 W (typ), 240 W (max)
Power Saving Mode	< 1 W

## MECHANICAL SPECS

Bezel Width (T/B/L/R)	Even bezel 10.9 mm
Cabinet Color	Black
Dimension (LxHxD, w/o stand)	1240 x 710 x 87.7 mm
Weight (set/package)	27.5kg / 32.5kg
VESA Mounting (dimension)	400 x 400 mm
Orientation	Portrait / Landscape

## USER INTERFACE

Language	English
Daisy Chain	DVI, RS-232
Proof of Image Retention	Yes
Dimming Control (DCR)	Yes
Built-in Video Wall Support	Up to 15x15
ID Setting for Daisy Chain	Yes
On/Off Scheduling	Yes
Ambient Light Sensor	Yes
Total Turn-on time	Yes
Internal Temperature Sensor	Yes
Network Control	RS-232(IN/Out), RJ45
OSD Menu Rotation	Yes
Carrying Handles	Yes
Fanless desing	Yes
Polarized sunglasses support	Yes

## I/O PORTS

DVI-D	In (x1), Out (x1)
Display Port	In (x1)
HDMI	In (x1)
RS-232	In (x1), Out (x1)
RJ-45	In (x1)
Audio	In (x1), Out (x1)
USB	USB2.0 for Internal Player*
SD Card Slot	For Internal Player*

## ACCESSORIES

Included Accessories	Power Cord, Remote controller, ESK302, QSG
----------------------	--

## ENVIRONMENT

Operating Temperature	0° C ~ 45° C
Storage Temperature	-20° C ~ 60° C
Humidity	10% ~ 80% RH Non-condensing

## CERTIFICATION

CE / FCC ClassB / ROHS

## INTERNAL PLAYER

Processor	ARM Cortex-A9 1.6 GHz, Quad-Core CPU
On chip cache memory	L2: 512KB
Clock speed	1.6GHz
Main memory interface	1GB DDR3/3L (1600MHz)
Graphics	600M ARM Mali400MP4,2D/3D graphic engine, support OpenGL ES1.1/2.0, Open VG1.1
Storage (FDM)	8GB NAND Flash(2GB occupied by o/s, 6GB available depending on
Multimedia	H.264 encoder/decoder, MPEG-1/2/4, H.263, H.264 MVC, AVS, VC-1, VP8/6, RV
IO ports	USB 2.0, SD slot
Operating system	Yes

# 55" HIGH BRIGHTNESS 3500 NIT FANLESS LCD WITH NARROW BEZEL MODEL DS552LT4-1

