

Key features



- Up to 450Mbps on 2.4GHz and up to 1300Mbps on 5GHz
- Supports IEEE802.11a/b/g/n and ac (draft) standards
- Band steering shifts dual-band clients to 5GHz for better throughput performance
- Sectorized 3D antenna design

The EWS360AP can operate as a stand-alone access point connecting to third-party PoE-capable switches but more control and versatile management of the access point is achievable when it is part of an EnGenius Neutron-series wireless network management solution because the AP includes firmware that enables it to be immediately discovered, configured, monitored and managed from a compatible Neutron Series PoE+ switch (EWS5912FP, EWS7928FP or EWS7952FP).

This capability enables IT managers to deploy and manage up to 50 EWS360APs from a the Neutron-series switch allowing for simplified management from one browser-based interface including simultaneous firmware upgrades, clustering, traffic monitoring, bandwidth steering and many other features that can be reset or reconfigured from the convenience of the IT manager's desktop.

Operating in both the 2.4GHz and 5GHz frequency spectrums and supporting 802.11a/b/g/n and ac (draft) standards the EWS360P features wireless speeds up to 450Mbps on the 2.4GHz radio and up to 1300Mbps on the 5GHz radio. A Gigabit port for connecting to 802.3at-capable PoE switches, and an enhanced receive sensitivity MIMO (Multiple In/Multiple Out) antenna array. As a result, the EWS360AP is ideal for spacious environments such as large homes, small and medium-sized businesses, multiple-floor offices, hotels, hospitals, and other multi-floor buildings.

As the EWS360AP is designed for deployments on ceilings where power outlets may be scarce, it also comes equipped with PoE (Power-over-Ethernet) IEEE 802.3at for use with an 802.3at-capable PoE injector or 802.3at-capable PoE switches, drawing up to 22watts of power.

Paired with other Neutron-series access points and switches, the EWS360AP helps to make managing a network easier with its standardized GUI. To protect sensitive data during wireless transmissions, the EWS360AP offers different industry-standard encryption settings for wireless transmissions, including WEP, WPA-PSK, WPA2-PSK, WPA-PSK Mixed, WPA Enterprise, WPA2 Enterprise, and WPA2 Mixed enterprise. It also includes MAC address filtering to allow network administrators to offer network access only to verified computers and devices based on their MAC addresses.

Technical specifications

Hardware

RF: 2.4GHz and 5GHz frequency bands
Standard: IEEE 802.11a/b/g/n/ac (draft)
Radio I: 11b/g/n: 2.412~2.484GHz
Radio II: 11a/n: 5.18-5.24 and 5.26-5.32 and 5.5-5.7 and 5.745-5.825GHz
Data rate: Up to 450Mbps in the 2.4GHz frequency band;
Up to 1300Mbps in the 5GHz band
Memory: 128MB

Flash memory: 16MB

Antenna

3* 3dBi 2.4GHz antennas

3* 5dBi 5GHz antennas

Physical interface

1* RJ-45 Gigabit Ethernet
(10/100/1000 Mbps) - PoE capable

1* Reset button

1* Power connector

Power requirements

Power supply: 100 to 240 VDC \pm 10%,
50/60 Hz (depends on different countries)

Active Ethernet

(Power-over-Ethernet, IEEE 802.3at)

Power adapter (United States) 48VDC/0.375A

Device: 12V/2A

Modulations

OFDM: BPSK, QPSK, 26-OAM, 64-QAM, DB-PSK, DQPSK, CCK

Operating channels

2.4 GHz: US/Canada 1-11

5 GHz: Country dependent for the following ranges:

36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 149, 153, 157, 161, 165

Management

Operation modes

Access point, Mesh AP (available soon)

Multiple BSSID

Supports up to 8 BSSIDs per radio

LAN

IP (check validity and DHCP server IP range)
MAC

Spanning Tree

Supports 802.1d Spanning Tree Protocol

Wireless

Wireless mode: 11a/11b/11g/11n/11ac
Channel selection (settings vary by country)
Channel bandwidth (Auto, 20 MHz, 40 MHz)

Transmission rate

2.4GHz: 11n only, 11b/b/n mix, 11b only, 11b/g, 11g only

5GHz: 11n only, 11a/n mix, 11a only

QoS

WMM (Wireless Multimedia)

Wireless management features (with Neutron-series switch)

- Access point Auto discovery and provisioning
- Access point Auto IP assignment
- Access point cluster management
- Remote access point rebooting
- Access point device name editing
- Access point radio settings
- Band steering
- Traffic shaping
- Fast handover
- Fast roaming
- Access point client limiting
- Mesh network
- Wireless security (WEP, WPA/WPA2 Enterprise, WPA/WPA2 PSK)
- Guest network
- Access point status monitoring

- Wireless client monitoring
- Wireless traffic & Usage statistics
- Real-time throughput monitoring
- Visual topology view
- Floor plan view
- Map view
- Secure control messaging
- SSL certificate
- Local MAC address database
- Remote MAC address database (RADIUS)
- Unified configuration import / export
- Bulk Firmware upgrade capability
- Intelligent diagnostics

Management (cont.)

Tx Power control

Adjust transmit power by dBm

Configuration

Web-based configuration(http)

Firmware upgrade

Via web browser, settings are reseed after upgrade

Administrator settings

Administrator username and password change

Reset settings

Reboot (press and hold 2 seconds)

Reset to factory default (press and hold for 10 seconds)

System monitoring

Status statistic and event log

SNMP:

V1,V2c,V3

MIB

MIB I, MIB II(RFC1213) and private MIB

Traffic shaping

Incoming and outgoing wireless traffic shaping

Auto-channel selection

Automatically selecting least congested channel

Bandwidth measurement

IP range and bandwidth management

Auto reboot

Reboot access point by minute, hour, day or week

Back up and restore

Save and restore settings through Web interface

CLI:

Supports command line interface

Diagnosis:

IP pinging statistics

Log:

Syslog and Local log support

LED Control:

On/Off

AP Detection:

Scanning for available EnGenius APs

Wireless security

WPA/WPA2 Personal(WPA-PSK using TKIP or AES)

WPA/WPA2 Enterprise(WPA-PSK using TKIP)

802.1x RADIUS authenticator: MD5/TLS/TTLS, PEAP

SSID broadcast enable/disable

MAC address filtering (WLAN, up to 50 field)

L2 isolation (Access point mode)

QoS (Quality of Service)

WMM (Wireless Multimedia)

Environment & mechanical

Temperature range: 0°C to 50°C

Operation: -20°C to 60°C storage

Humidity: (non-condensing) 90% or less

Operating: 90% or less storage

Certifications

FCC,IC

Package content

EWS360AP dual band AC1750

Indoor access point

12V/2A power adapter

T-rail mounting kit

Ceiling mount and wall screw kit

Mounting bracket

RJ-45 Ethernet cable

Quick installation guide.