



Key features

- Dynamic channel optimization
- Internal high gain antenna
- Band steering shifts dual-band clients to 5GHz for better throughput performance
- Fast handover

High power, high sensitivity and high reliability solution designed to operate under harsh environments

The EWS660AP is a versatile, high power outdoor access point designed to withstand harsh environments making it an ideal solution for creating outdoor wireless networks. With transfer rates of up to 1300Mbps in 5GHz and 450Mbps in 2.4GHz, users are able to enjoy faster wireless connections for bandwidth hungry applications such as audio, video and voice streaming. With its IP55-rated waterproof enclosure and the flexible mounting capabilities, this product is suitable to be installed in stadiums, school campuses, stations, airports, manufacturing plants or virtually any venue requiring a robust outdoor wireless solution.

Enhanced signal strength to further extend WLAN coverage

Equipped with built-in high-gain antennas designed for high power radio, the EWS660AP has been enhanced to provide higher signal strength and sensitivity; this will assist to reduce dead spots in your deployed WLAN and boost received signal quality on both ends of AP and wireless client devices.

802.3at Power over Ethernet (PoE) support

The EWS660AP can be powered using the enclosed PoE injector or any off-the-shelf 802.3at-compliant PoE switches, solving the common power sourcing issue in the field where devices are usually placed in outdoor environment. With PoE power management from the EWS management switch, the power budget of the EWS660AP and its consumption can be configured and monitored immediately.

Wireless radio specification

Dual radio, 5GHz 802.11a/n/ac and 2.4GHz 802.11b/g/n

- 2.4GHz: Max 450Mbps
 - 5GHz: Max 1300Mbps
 - Dual concurrent radio support
- Transmit power (maximum value)*
- 2.4GHz/5GHz: Max 28dBm
 - Maximum power is limited by regulatory power

Supported radio technologies

- 802.11b: direct-sequence spread-spectrum (DSSS)

- 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)

- 802.11n/ac: 3x3 MIMO with 3 streams
- 802.11ac with 20/40/80MHz channel width
- 802.11n with 20/40MHz channel width
- 802.11a/b/g with 20MHz channel width

Supported modulation types

- 802.11b: BPSK, QPSK, CCK
- 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM
- 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

Supported data rates (Mbps)

- 802.11b: 1, 2, 5.5, 11
- 802.11a/g: 6, 9, 12, 18, 36, 48, 54
- 802.11n: 6.5 to 450 (MCS0 to MCS23)
- 802.11ac: 6.5 to 1,300 (MCS0 to MCS9, NSS=1 to 3)

Power

Power source

- 802.3af/at compliant source
- Active Ethernet (Power over Ethernet, PoE)

Antennas

Internal high gain antennas

- 3T3R 5dBi dual concurrent omni antenna

Interface

Two 10/100/1000 BASE-T Ethernet Port

- LAN1 supports 802.3af/at PoE input
- LAN2 is used to extend Internet signal

Reset button

Mechanical & environment

Dimensions/Weight

- 300mm (L) x 181mm (W) x 34.1mm (H)

Operating

- Temperature: -20°~70°C

Harsh environment use

- IP55 rated

Operation mode

A variety of operation modes to serve multiple constituencies and applications. (Access point, WDS and Mesh (future firmware)).

Easy management

Auto channel selection

- Setting varies by regulatory domains.

SSIDs

- BSSID support
- 16 SSIDs support
- Supports 8 SSIDs on both 2.4GHz and 5GHz band

SNMP & MIB

- v1/v2c/v3 support, MIB I/II, Private MIB

Save configuration as default

- Saves the customized configuration as default value for different customer demands.

Clients traffic status

- Reports the various main information timely which is required by administrator.

Guest network

- Allows the administrator to manage easily grant "visitor" access within the network.

E-mail alert

- Provides a network monitoring tool for administrators to stay informed the configuration change.

QoS

- Compliant with IEEE802.11e standard

RADIUS accounting

- Help operators to offload 3G to Wi-Fi seamlessly

Effective control and use

CLI comments support

- Setting varies by regulatory domains

Distance control (Ack Timeout)

Multicast supported

Wi-Fi scheduler

- Set the schedule for rebooting the device

Band steering

- Shift the clients from 2.4GHz band to 5GHz band when the clients contest in 2.4GHz band

Fast roaming

- Minimize perceptible delay during re-association.

Fast handover

- Steer clients from the AP to other APs under the same encryption and SSID when the signal is above the default value.

Reinforcement security

WEP Encryption: 64/128/152 bit

WPA/WPA Enterprise (WPA-EAP using TKIP or AES)

Hide SSID in beacons

MAC address filtering

- Filter up to 32 MACs per SSID

Wireless STA (client) connection list

- Reports the various main information timely which is required by administrator

HTTPS

- Widely used communications approach for securing communication over a computer network.

SSH

- Provide confidentiality and integrity of data over an unsecured network, such as the Internet.