

Connect and control, right where you are



No cables on the floor
AV cables (1.7 m) pull out and retract easily for storage

Standard version connects
HDMI, VGA, 3.5 mm audio
mini-jack, network cable
(RJ45) and USB-A

Direct-out 12V power supply

One AC power connector:
EU, Universal or DK power

Direct access to AV control
functions with Neets
Control - EcHo integration

Easy to use - choose source,
start presentations, roll
down screens and dim the
light with one button

Automatic timer functions
can switch a projector or a
screen off after a period of
inactivity or auto shut down
when no motion is detected

All eight buttons can be
configured for any function



Neets EasyConnect - EcHo solves one of the most common problems encountered in AV presentations: When a guest presenter wants to connect a laptop computer, the proper cables are missing, or they are too short, or the connection point is hidden away in a floor pocket or wall panel.

The EasyConnect is the obvious solution. All necessary connections are readily accessible, right on the tabletop, inside a durable metal enclosure.

The standard version accommodates all five typical connections for laptop



computers and most tablet-type mobile devices. The integrated AC power receptacle eliminates the need to find extension cords for connecting to distant wall outlets.

The EasyConnect - Control is sold as a package including a Neets AV system control module.

With the integrated Neets Control - EcHo AV control system, starting a presentation is quick and frustration-free: Just plug in the required cables, press the corresponding control buttons, and the projector starts, screen lowers, and the correct PC is selected.

Default cables included:

3.5 mm audio

HDMI

USB-A

VGA

Cat-5 type (RJ45)

Cat-5 type (RJ45)



AC power connector choices:



EU "schuko"
power socket



Universal
power socket



DK
power socket

Technical specifications:

Neets EasyConnect - Control:

Direct access to AV control functions w/ Neets Control EcHo or SieRRa integration

Direct-out 12V power supply

Enclosure type:

Metal (steel box with cast aluminum top and lid)

Sliding cover with cable pass-through

Default cables:

HDMI, VGA, 3.5 mm audio, USB-A, Cat-5 type (RJ45)

AC power connector:

EU, Universal or DK power connector

Dimensions:

Recessed box:

Please see illustrations in the EasyConnect manual

Top plate:

Width: 252 mm

Depth: 135.5 mm

Weight:

2.15 kg

Neets Control - EcHo:

Communication ports:

1 X RS-232 (TX and RX)

Baud: 1200 – 115200

Data Bit: 7/8

Parity: None, Even, Odd

Stop Bit: 1/1.5/2

1 x RS-232 or IR (TX only)

RS-232

Baud: 1200 – 115200

Parity: None, even, odd

Stop Bit: 1/1.5/2

IR:

Transmit

381 Hz – 500 kHz

Devices: 2

3 x input/Output:

input:

sense Low: <1 VDC

Sense High: >4 VDC

Output:

Type: Open drain

Max Voltage: 24 VDC

Max Current: 0.5 A

Conformity:

Approval: CE

EN 55022

EN 55024

Product item numbers:

305-0200 EasyConnect - EcHo EU, includes a set of default cables, Neets Control - EcHo and EU power socket.

305-0205 EasyConnect - EcHo, includes a set of default cables, Neets Control - EcHo and universal power socket.

305-0202 EasyConnect - EcHo DK, includes a set of default cables, Neets Control - EcHo and DK power socket.