



HD / 1,280 x 960 H.264 Vandal Resistant Network Camera featuring *Super Dynamic* (WV-SW155)

SVGA / 800 x 600 H.264 Vandal Resistant Network Camera featuring *Super Dynamic* (WV-SW152)

Key Features

- 720p HD images up to 30 fps (WV-SW155)
- 1.3 Megapixel high sensitivity MOS Sensor
- Super high resolution at SVGA/800 x 600 created by 1.3 Megapixel high sensitivity MOS Sensor (WV-SW152)
- Multiple H.264 (High profile) streams and JPEG streams ensure simultaneous real time monitoring and high resolution recording by "UniPhier[®]", Panasonic's proprietary System LSI platform.
- Full frame (Up to 30 fps) transmission at 1,280 x 960 image size (WV-SW155)
- Full frame (Up to 30 fps) transmission at SVGA (800 x 600) image size (WV-SW152)
- **Super Dynamic** and ABS (Adaptive Black Stretch) technologies deliver 128x wider dynamic range compared to conventional cameras.
- **Face Super Dynamic** Range technology ensures clear face image.
- High sensitivity with Day & Night (Electrical) function:
 - 0.8 lx (Color), 0.6 lx (B/W) at F2.2 (WV-SW155)
 - 0.6 lx (Color), 0.4 lx (B/W) at F2.2 (WV-SW152)
- VIQS (Variable Image Quality on Specified area) technology allows the designated area to retain higher image quality while the excluded area will have a decreased image quality, which enables to use lower image file size and bit rate.
- Digital Noise Reduction: 3D-DNR ensures noise reduction in various conditions.
- Progressive scan ensures clear images with less motion blur and no tearing even when the subject is moving.
- Electronic sensitivity enhancement: Auto (Up to 16x) / OFF
- Selectable light control modes: Indoor scene (50 Hz) / Indoor scene (60 Hz) / ELC (maximum exposure time)
 - Indoor scene (50 Hz/60Hz): Flicker caused by fluorescent lightning will be automatically compensated.
 - ELC (maximum exposure time): The lightning control will be automatically performed by adjusting shutter speed in the range of ELC.
- 2x extra zoom under VGA resolution
- 2x, 4x digital zoom controlled by browser
- VMD (Video Motion Detection) with 4 programmable detection areas, 15 steps sensitivity level and 10 steps detection size
- Face detection function detects the position of human face and the information is sent by XML or video stream.
- Meta data for VMD works with the WJ-ND400 playback VMD function.

- Privacy Zone can mask up to 2 private areas, such as house windows and entrances/exits.
- Camera title display: Up to 20 alphanumeric characters on the browser
- Alarm sources including VMD and Panasonic alarm command can trigger actions such as FTP image transfer, E-mail notification, Indication on browser, and Panasonic alarm protocol output.
- JPEG Image compression ratio can be changed by alarm so that higher quality image can be provided.
- Prioritized stream control: One of the video streams can be prioritized when multiple recorders or client PCs are accessing the camera so that the recorder or the client PC can maintain the frame rate.
- SDHC/SD Memory card slot for manual recording (H.264 / JPEG), alarm recording (H.264 / JPEG) and backup upon network failure (JPEG)
- H.264 max. bit rate/client and Total bit rate control allows flexible network traffic management. Frame rate priority mode controls bit rate and compression ratio to provide the specified frame rate.
- Internet mode: H.264 images can be transmitted over HTTP protocol.
- Multi-language: English / Italian / French / German / Spanish / Russian / Chinese / Japanese
- IPv4/IPv6 protocol supported
- Supports SSL, DDNS (viewnetcam, RFC2136)
- Still images (JPEG) can be viewed on mobile phones via Internet.
- ONVIF compliant model
- Low profile design for discrete installation
- "Railway applications – Electronics equipment used on rolling stock" compatible with EN50155
- Wide coverage (Horizontal: 104 °, Vertical: 85 °)
- IP66 rated water and dust resistant. Compatible with IEC60529 measurement standard.
- Vandal resistant mechanism for high reliability

Standard Accessories

• Installation Guide	1 pc.	• Mount Bracket.....	1 pc.
• Important Safety Instructions.....	1 pc.	• Tamperproof Screw Bit	1 pc.
• CD-ROM*1	1 pc.	• Waterproof Tape	1 pc.
• Code Label*2	1 pc.		
• Lens adjuster.....	1 pc.		

The followings are for installation.
 • Fixing Screws (M4 x 8 mm)3 pcs.
 • Installation Template Label1 pc.

*1 The CD-ROM contains the operating instructions and different kinds of tool software programs.
 *2 This label may be required for network management. The network administrator shall retain the code label.


Specifications

TV System	NTSC	PAL
Camera	1/3 type MOS Sensor Effective Pixels: Approx. 1.3 megapixel Scanning Mode: Progressive Scanning Area: 4.8 mm (H) x 3.6 mm (V) (3/16" (H) x 5/32" (V)) Minimum Illumination: WV-SW155: Color: 0.8 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.05 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High)) *1 WV-SW152: Color: 0.6 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.04 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High)) *1 White Balance: AWC (2,000 - 10,000 K), ATW1 (2,700 - 6,000 K), ATW2 (2,000 - 6,000 K) Light Control Mode: Indoor scene (50 Hz / 60 Hz) / ELC Shutter Speed: With Super Dynamic ON: ELC (1/30 s) With Super Dynamic OFF: ELC (1/30 s), ELC (3/100 s), ELC (3/120 s), ELC (2/100 s), ELC (2/120 s), ELC (1/100 s), ELC (1/120 s), ELC (1/250 s), ELC (1/500 s), ELC (1/1,000 s), ELC (1/2,000 s), ELC (1/4,000 s), ELC (1/10,000 s) Super Dynamic: ON / OFF Face Super Dynamic: ON / OFF (Only at Super Dynamic: ON) Adaptive Black Stretch: ON / OFF AGC: ON (HIGH) / ON (MID) / ON (LOW) / OFF Electronic Sensitivity UP: OFF (1/30 s), Max. 2/30 s, Max. 4/30 s, Max. 6/30 s, Max. 10/30 s, Max. 16/30 s Day & Night(electrical): OFF / AUTO Dynamic Range: 52 dB typ. (Super Dynamic: ON, Light Control: ELC) Digital Noise Reduction: HIGH / LOW Video Motion Detection: ON / OFF, 4 areas available Privacy Zone: ON / OFF (up to 2 zones available) VIQS: ON / OFF Camera Title (OSD): Up to 20 characters (alphanumeric characters, marks), On/Off Focus Adjustment: MANUAL	
Lens	Focal Length: 1.95 mm Zoom Ratio: 1x / Extra zoom: 2x (under VGA resolution) Angular Field of View: Horizontal: 104 °, Vertical: 85 ° Maximum Aperture Ratio: 1 : 2.2 Focusing Range: 0.5 m ~ ∞	
Adjusting Angle	Ceiling Installation Horizontal: -20 ° to +20 ° Vertical: -20 ° to +90 ° Wall Installation Horizontal: -80 ° to +80 ° Vertical: -90 ° to +20 °	
Browser GUI	Camera Control: Brightness Display Mode: Spot, Quad: Image from 16 cameras can be displayed in 4 different Quad screens or 16 split screen (JPEG only). 20 characters camera title available. Digital Zoom: 1x, 2x, 4x controlled by browser GUI Camera Title: Up to 20 alphanumeric characters Clock Display: Time: 12H/24H, Date: 5 formats on the browser, Summer time (Manual) One Shot Capture: A still picture will be displayed on a newly opened window. SD Memory Data Download: Still or motion Images recorded in the SDHC/SD memory card can be downloaded. GUI/Setup Menu Language: English, Italian, French, German, Spanish, Chinese, Russian, Japanese System Log: Up to 100 (Internal), Up to 4,000 (SDHC/SD memory when the recording format is set to JPEG.) error logs Supported OS *2 *3: Microsoft® Windows® 7, Microsoft® Windows Vista®, Microsoft® Windows® XP SP3 Supported Browser: Windows® Internet Explorer® 9.0 (32 bit), Windows® Internet Explorer® 8.0 (32 bit), Windows® Internet Explorer® 7.0 (32 bit), Microsoft® Internet Explorer® 6.0 SP3	
Network	Network I/F: WV-SW155 / WV-SW152: 10Base-T / 100Base-TX, RJ-45 connector (female) WV-SW155M / WV-SW152M: 10Base-T / 100Base-TX, M12 connector (male) Image Resolution *3 *4: Aspect ratio: WV-SW155: H.264: 1,280 x 960 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps JPEG: 1,280 x 960 / 640 x 480 / 320 x 240, up to 30 fps WV-SW152: H.264: 800 x 600 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps JPEG: 800 x 600 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps Aspect ratio: [16 : 9] WV-SW155: H.264: 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps JPEG: 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps WV-SW152: H.264: 640 x 360 / 320 x 180, up to 30 fps JPEG: 640 x 360 / 320 x 180, up to 30 fps H.264/MPEG-4 *5 *6: Transmission Mode: Constant bitrate / Framerate priority / Best effort Frame Rate: 1 / 3 / 5 / 7.5 / 10 / 15 / 20 / 30 fps 1 / 3 / 5 / 7.5 / 10 / 12 / 15 / 20 / 30 fps Bit Rate/Client: 64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 1,536 / 2,048 / 3,072 4,096 / 8,192* kbps * H.264 mode only (WV-SW155) Image Quality: LOW / NORMAL / FINE Transmission Type: UNICAST / MULTICAST JPEG: Image Quality: 10 steps Refresh Interval: 0.1 fps ~ 30 fps Transmission Type: PULL / PUSH Total Bit Rate: 64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 2,048 / 4,096 / 8,192 kbps / Unlimited Supported Protocol: IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, RTP, FTP, SMTP, DNS, NTP, SNMP, DHCPv6 IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTSP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP	


TV System	NTSC	PAL
Network	FTP Client: Alarm image transmission, FTP periodic transmission (When the FTP transmission is failed, backup on an optional SDHC/SD memory card is available.) No. of Simultaneous Users: Up to 14 users (Depends on network conditions) SDHC/SD Memory Card (Option): Manufactured by Panasonic SDHC memory card: 4 GB, 8 GB, 16 GB, 32 GB SD memory card: 256 MB, 512 MB, 1 GB, 2 GB microSD card and microSD card Face Detection: ON / OFF (with XML notification) Cellular Phone Compatibility: JPEG image Mobile Terminal Compatibility: iPad, iPhone, iPod touch	
Alarm	Alarm Source: VMD, Command alarm Alarm Actions: SDHC/SD memory recording, E-mail notification, Indication on browser, FTP image transfer, Panasonic protocol output Alarm Log Schedule: With SDHC/SD memory card: 5,000 logs, without SDHC/SD memory card: 1,000 logs VMD	
General	Safety/EMC Standard: UL (UL60950-1), FCC (Part15 ClassA), CE, IEC60950-1 (EN55022 ClassB, EN55024) C-UL (CAN/CSA C22.2 No.60950-1), DOC (ICES003 ClassA) Power Source and Power Consumption: PoE (IEEE802.3af compliant) / PoE 48 V: 56 mA (Class 1 device) Ambient Operating Temperature: -30 °C ~ +50 °C (-22 °F ~ 122 °F) Ambient Operating Humidity: Less than 90 % (no condensation) Impact Protection: IEC 60068-2-75 test Eh, 50 J / IEC 62262 IK10 Water and Dust Resistance: Camera: IP66 (IEC60529) *5 Railway Application: EN50155, EN50121 Dimensions: ø109 mm x 47 mm (H) (ø6-15/32" x 5-3/4" (H)) Mass (approx.): 350 g (0.77 lbs.) Finish: Main body: Aluminum die cast, light gray, Dome section: Clear polycarbonate resin	

- *1 Converted value
 *2 Refer to "Notes on Windows Vista® / Windows® 7 on the provided CD-ROM for further information about system requirements for a PC and precautions when using Microsoft® Windows® 7 or Microsoft® Windows Vista®.
 *3 When using IPv6 for communication, use Microsoft® Windows® 7 or Microsoft® Windows Vista®.
 *4 Transmission for 2 streams can be individually set in the same compression method.
 *5 Only when installation work specified in this book is properly performed and appropriate waterproof treatment is performed.

Part Names and Functions



Appearance



Trademarks and registered trademarks

- Microsoft, and Windows are registered trademarks of Microsoft Corporation in the U.S. and other countries.
- iPad, iPhone and iPod touch are registered trademarks of Apple Inc.
- ONVIF and the ONVIF logo are trademarks of ONVIF Inc.
- UniPhier is a registered trademark of Panasonic Corporation.
- "Super Dynamic", "SDII", "SDIII", "SD5", "SD5Link", "i-PRO" and "i-PRO SmartHD" logos are trademarks or registered trademarks of Panasonic Corporation.

Important

- Safety Precaution: carefully read the operating instructions and installation manual before using this product.
- Panasonic can not be responsible for network performance and/or other manufacturer products that reside on the network.

- All TV pictures are simulated.
- Masses and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.
- All product pictures are NTSC models.

DISTRIBUTED BY:

Panasonic®

<http://panasonic.net/security/>

Printed in Japan (2A-079A)