



Sierra Wireless® AirLink® LS300 Industrial Gateway

BENEFITS

- Intelligence that makes it quick to deploy and simple to manage
- Reliable connectivity that ensures it stays connected to the network
- Rugged design that lasts for years in the harshest environments
- Application framework that makes it easy to program
- Integration with AirLink Management Service (ALMS) for building innovative applications and services
- 3-year warranty

Compact industrial 3G gateway

The AirLink® LS300 industrial gateway has a small footprint for easy installation and a rugged, military spec design (MIL-STD 810) that enables it to withstand extreme temperature changes, humidity, shock, and vibration. Certified for hazardous environments (Class I, Div 2), the LS300 is ideal for industrial deployments.

The LS300 comes standard with Ethernet, USB and serial interfaces, as well as digital I/O and GPS, enabling you to:

- Remotely monitor and control your infrastructure and surveillance equipment on pipelines, meters, pumps and valves in any energy, utility or industrial application.
- Instantly connect your equipment at remote locations or temporary sites.
- Track the location of heavy equipment and assets in the field, while providing reliable internet connectivity to remote workers.

QUICKLY CONFIGURE AND DEPLOY

The comprehensive set of configurable options makes it quick and easy to deploy in the field. With ALEOS™ embedded intelligence, the LS300 can be deployed in most industrial applications out-of-the-box.

In addition to configuring connection settings, ALEOS enables users to setup custom security, networking, and routing parameters, GPS location tracking, and events reporting without any programming. With a proven 20-year track record of over a million deployed devices, ALEOS has been developed to ease integration and configuration for a wide range of deployment scenarios.

ADD CUSTOM LOGIC WITHOUT ANY EMBEDDED EXPERTISE

ALEOS Application Framework and integrated development environment make it easy to process data inside the LS300. Collect and analyze information from connected equipment and optimize data transfers using a simple, Lua-based scripting language. Now you can program an AirLink gateway without deep embedded expertise.

Specification	
3G HSPA+ MODELS	Fallback to GSM/GPRS/EDGE <ul style="list-style-type: none"> 800/850/1900/2100 MHz HSPA+ Sierra Wireless SL8090 Radio Module 900/2100 MHz HSPA+ Sierra Wireless SL8092 Radio Module Peak HSPA data rates <ul style="list-style-type: none"> Download: 14.4 Mbps Upload: 5.76 Mbps
3G EV-DO MODELS	Fallback to CDMA 1xRTT <ul style="list-style-type: none"> Rev. A 800/1900 MHz Sierra Wireless SL5011 Radio Module Peak CDMA data rates <ul style="list-style-type: none"> Download: 3.1 Mbps Upload: 1.8 Mbps
CARRIER APPROVALS	Approved for deployment by Verizon, AT&T, Sprint, Rogers, Bell, and Telus
HOST INTERFACES	10/100 Base-T RJ45 Ethernet RS-232 serial port USB V2.0 Micro-B connector 2 SMA antenna connectors (Primary, GPS/Diversity) Active antenna support PPPoE
INPUT/OUTPUT	Configurable I/O pin on power connector <ul style="list-style-type: none"> Digital Input ON Voltage: 3.3 to 30 VDC Digital Input OFF Voltage: 0 to 1.2 VDC Analog Input Voltage 0 to 30 VDC Open collector output > 200mA @ 30VDC
GPS TECHNOLOGY	HSPA+ Models <ul style="list-style-type: none"> Acquisition Time: <3 Sec Hot Start, <45 Sec Cold Start Accuracy: <10m Tracking Sensitivity: -155 dBm EV-DO Models <ul style="list-style-type: none"> Acquisition Time: 9 sec Hot Start, <39 Sec Cold Start Accuracy: <3m (50%), <8m (90%) Tracking Sensitivity: -160 dBm
PROTOCOLS	Network: TCP/IP, UDP/IP, DNS Routing: NAT, Host Port Routing, DHCP, PPPoE, VLAN, VRRP, Reliable Static Route Application: SMS, Telnet/SSH, Reverse Telnet, SMTP, SNMP, Sntp Serial: TCP/UDP PAD Mode, Modbus (ASCII, RTU, Variable), PPP GPS: NMEA 0183 V3.0, TAIP, RAP

Specification	
EVENTS REPORTING	Event Types: Digital Input, GPS/AVL, Network Parameters, Data Usage, Timer, Power, Device Temperature Report Types: SMS, Email, SNMP Trap, Relay Output, GPS Rap Report, Events Protocol Message to Server
VPN/SECURITY	IPsec, SSL, and GRE VPN Client Up to 5 VPN Tunnels IKE Encryption Port Forwarding and DMZ Port Filtering Trusted IP MAC Address Filtering
DEVICE MANAGEMENT	AirLink Management Service cloud-based device management application ACEManager™ device configuration utility
DIMENSIONS	3.0 in x 3.5 in x 1.0 in (76 mm x 90 mm x 25 mm) 6.7 oz (190G)
POWER CONSUMPTION	All figures in mA @ 12VDC <ul style="list-style-type: none"> HSPA+: Idle 224, Typ 245, Max 430 CDMA: Idle 220, Typ 257, Max 427 Low Power Standby Mode: <68 Analog Ignition Sense & Power Management Input Voltage: 7 to 28 VDC
ENVIRONMENTAL	Operating Temperature: -30°C to +70°C / -22°F to +158°F Storage Temperature: -40°C to +85°C / -40°F to +185°F Humidity: 90% RH @ 60 °C Military Spec MIL-STD-810 conformance to thermal, mechanical shock and humidity
INDUSTRY CERTIFICATIONS	PTCRB, R&TTE, FCC, Industry Canada, CE, RoHS Compliant, Class 1 Div 2.

About Sierra Wireless

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, and 4G embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster.

For more information, visit www.sierrawireless.com.