

Spectralink IP-DECT Base Station

Over the air call signalling between your DECT server and handsets



The Spectralink IP-DECT Base Station controls the traffic in the air and provides the link between Spectralink wireless handsets and Spectralink DECT Servers. The Spectralink IP-DECT Base Station interoperates with the entire Spectralink DECT Server portfolio.

Spectralink DECT Servers power the Spectralink IP-DECT Base Stations through standard Power over Ethernet (PoE) LAN cables or an external power supply can be used.

Each Spectralink IP-DECT Base Station has 12 speech channels and covers a circular area between 20-300 meters (66 and 985 feet) in diameter. Because coverage depends on location specifics such as building materials and interference, a site assessment before installation helps to determine the proper number and placement of base stations.

SPECIFICATIONS

NETWORK AND PROVISIONING

- 10/100 Mbps Ethernet port
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronisation from the Spectralink DECT Server
- Event logging
- LED status indication

RADIO INTERFACE

- RF Output 20 to 24 dBm at antenna connection
- Sensitivity: typical -90 dBm measured at antenna connection at BER =0.001
- Typical range:
 - Indoor: 20-50 m. (65.6 - 164 ft.)
 - Outdoor: 300 m. (984.3 ft.)
- Zero blind slot channels (12 channels)

ELECTRO MAGNETIC COMPATIBILITY APPROVALS (REGULATORY STANDARDS)

- EN 301 489-1
- EN 301 489-6
- FCC RULES, FCC PART15, SubpartD; RSS-213
- IC Rules RSS213 Issue 2

The Spectralink IP-DECT Base Station is regulatory-certified for frequency bands used in North America, Europe, Australia and New Zealand.

Learn More

Learn what Spectralink wireless telephones can do for your organisation. Visit us at spectralink.com or contact your Spectralink representative.

SAFETY (REGULATORY STANDARDS)

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1

DECT APPROVAL

- EN 301 406

ELECTRICAL REQUIREMENTS

- Power over Ethernet (IEEE 802.3af), Class 1 device
- Typical power consumption: 2W per unit
- External power supply option
- External antenna connection

ENVIRONMENTAL CONDITIONS

- Operating temperature: -10° - 40° C (50° - 104° F)
- Storage temperature: -50° - 70° C (-58° - 158° F)
- Relative humidity: Between 20% and 80% (non-condensing)
- The equipment is in compliance with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

PHYSICAL CHARACTERISTICS

- Size: 100 x 38 x 100 mm (3.9 x 1.2 x 3.9 in.)
- Weight: 120 gr. (4.2 oz)
- Grey-white (NCS 0502-Y)
- Wall-mountable, indoor