

HARDWARE FEATURES

Interface	2 10/100/1000Mbps RJ45 Port AUTO Negotiation/AUTO MDI/MDIX 1 POWER OUTPUT PORT
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Power Supply	12VDC 1A, 9VDC 1A, 5VDC 2A
Basic Function	Compatible With IEEE 802.3af Compliant PSEs Delivers Power Up To 100 Meters Optional 12VDC, 9VDC or 5VDC Power Output
LED Indicator	PWR
Dimensions (W x D x H)	3.2*2.1*0.9 in.(80.8*54*24 mm)

SOFTWARE FEATURES

Basic Function	Compatible With IEEE 802.3af Compliant PSEs Delivers Power Up To 100 Meters Optional 12VDC, 9VDC or 5VDC Power Supply
----------------	---

OTHERS

Certification	FCC, CE, RoHS
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing