

Revolabs HD™ Single and Dual Channel Wireless Microphone System Product Specifications

Audio Bandwidth

- 50-20,000 Hz

Channels

- 1 or 2 channels per system

Radio Frequency

North America

- 1.92 to 1.93 GHz (UPCS North America)

International

- 1.88 to 1.90 GHz (DECT EU)

Range

- 150' (45 meters) approx. (no obstructions)
- Out-of-range alarm

HD Single/Dual Base Station Dimensions

- 5.19" (13.18 cm) x 3.25" (8.25 cm) x 1.0" (2.54 cm)
- 0.325 lbs (0.147 kg)

HD Single/Dual Base Station Connectors/ Interfaces



HD Single and Dual Base Station

1. Channel LED indicators
2. Pairing Push Buttons



3. USB port for Firmware Upgrades Only
4. Configuration DIP Switches (8)
5. Balanced Analog Output 3.5mm TRS connector
6. Balanced Analog Output 3.5mm TRS connector
7. Balanced Analog Input 3.5mm TRS connector
8. Balanced Analog Input 3.5mm TRS connector
9. Power In Connector-DC 5V

HD Single/Dual Base Station Power Requirements

- 100-240V, 50-60 Hz, 5W (Universal Inputs)

HD Single/Dual Charger Base Dimensions

- 4.6" (11.75 cm) x 3.125" (7.9 cm) x 1.0" (2.54 cm)
- 0.325 lbs (0.147 kg)

HD Single/Dual Charger Base Connectors

- Power In Connector-DC 5V
- 1 or 2 Proprietary 4 pin microphone charge jacks

HD Single/Dual Charger Base Power Requirements

- 100-240V, 50-60 Hz, 5W (Universal Inputs)



HD Single Charger Base



HD Dual Charger Base

Charge Time

- 2 hours

Encryption

- 128-bit proprietary (per microphone channel)

Environmental Requirements

Temperature

- 40° to 100° F (5° to 40° C) operating

Humidity

- 20% to 85%



HD Family of Wireless Microphones
From left to right:
XLR Adapter, Omni, Wearable, Directional,
Countryman Adapter



63 Great Road, Maynard, MA 01754
1-800-326-1088
www.revolabs.com
info@revolabs.com

Hear Every Word!