



# IB9367-H

Bullet Network Camera



2MP 30fps • SNV • WDR Pro • Smart Stream III •  
30M IR • IP66 • IP67 • IK10

The IB9367-H is the new professional outdoor IR bullet network camera from VIVOTEK, equipped with a full HD sensor capable of 1920x1080 resolution at 30 fps. With the most updated VIVOTEK SNV and WDR Pro technology, the IB9367-H is capable of capturing the highest quality images in both low light and high contrast environments.

The IB9367-H also offers great image in night time by equipping IR illuminators with effective range up to 30 meters. With an IP66, IP67 and IK10 rated housing, the IB9367-H is capable of operating under the harshest of conditions.

Additionally, the IB9367-H employs VIVOTEK's Smart Stream III technology and H.265 compression codec, reducing bandwidth more than 90%\* while still maintaining excellent image quality compared to traditional H.264 without smart streaming. Furthermore, the VIVOTEK VADP (VIVOTEK Application Development Platform) allows users to add customized programs for various applications and user scenarios.

\* Depending on scenes


## Key Features

- 30 fps @ 1920x1080
- H.265 Compression Technology
- Smart Stream III to Optimize Bandwidth Efficiency
- SNV (Supreme Night Visibility) for Low Light Conditions
- WDR Pro for Unparalleled Visibility in Extremely Bright and Dark Environments
- Built-in IR Illuminators, Effective up to 30 Meters
- Two-way Audio
- 3D Noise Reduction for Low-light Conditions
- Built-in MicroSD/SDHC/SDXC Card Slot
- Weather-proof IP66, IP67 and Vandal-proof IK10-rated Housing



Without WDR Pro

With WDR Pro



H.265 + Smart Stream III, Ultra-low Bandwidth

## Technical Specifications

Model	IB9367-H	<b>Audio</b>	
<b>System Information</b>		Audio Capability	Two-way audio
CPU	Multimedia SoC (System-on-Chip)	Compression	G.711, G.726
Flash	128MB	Interface	External Mic input External line output
RAM	512MB	<b>Network</b>	
<b>Camera Features</b>		Users	Live viewing for up to 10 clients
Image Sensor	1/2.8" Progressive CMOS	Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/ RTP/RTCP, IGMP, CIFS/SMB, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL/TLS, NTCIP
Maximum Resolution	1920x1080	Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
Lens Type	Fixed-focus	ONVIF	Supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>
Focal Length	f = 3.6 mm	<b>Intelligent Video</b>	
Aperture	F1.6	Video Motion Detection	Five-window video motion detection
Auto-iris	Fixed-iris	<b>Alarm and Event</b>	
Field of View	88° (Horizontal) 47° (Vertical) 104° (Diagonal)	Alarm Triggers	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection, MicroSD card life expectancy
Shutter Time	1/5 sec. to 1/32,000 sec.	Alarm Events	Event notification using digital output, HTTP, SMTP, FTP, NAS server and MicroSD card File upload via HTTP, SMTP, FTP, NAS server and MicroSD card
WDR Technology	WDR Pro	<b>General</b>	
Day/Night	Removable IR-cut filter for day & night function	Connectors	RJ-45 cable connector for Network 10/100 Mbps PoE connection Audio Mic in Audio line out DC 12V Digital input *1 Digital output *1
Minimum Illumination	0.07 Lux @ F1.6 (Color) 0.001 Lux @ F1.6 (B/W) 0 Lux with IR illumination on	LED Indicator	System power and status indicator
Tilt Range	90°	Power Input	DC 12V IEEE 802.3af PoE Class 0
Rotation Range	180°	Power Consumption	Max. 7 W
Pan/Tilt/Zoom Functionalities	ePTZ:48x digital zoom (4x on IE plug-in, 12x built in)	Dimensions	266 x 118 x 118 mm
IR Illuminators	Built-in IR illuminators, effective up to 30 meters with Smart IR, IR LED*2	Weight	1,142 g
On-board Storage	Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording	Casing	IP66, IP67, IK10 (Metal Housing)
<b>Video</b>		Safety Certifications	CE, LVD, FCC Class A, VCCI, C-Tick, UL
Compression	H.265, H.264, MJPEG	Operating Temperature	Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F)
Maximum Frame Rate	30 fps @ 1920x1080	Humidity	90%
Maximum Streams	3 simultaneous streams	Warranty	24 months
S/N Ratio	58 dB		
Dynamic Range	120 dB		
Video Streaming	Adjustable resolution, quality and constant bit rate control; Smart Stream III		
Image Settings	Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings, video rotation, 3DNR, DIS, HLC		

## Technical Specifications


### System Requirements

Operating System	Microsoft Windows 8/7
Web Browser	Mozilla Firefox 7~43 (streaming only) Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above Quicktime: 7 or above

### Included Accessories

Others	Quick installation guide, warranty card, screw pack, alignment sticker
--------	---

### Dimensions



## Compatible Accessories

### Mounting Kits



AM-312  
Pole Mount Adapter



AM-412  
Corner Mount Adapter



AM-719  
Junction Box